



# 235 Tractor



Compact with plenty of power and versatility, the Steiner 235 model tractor is game for any task. With a low center of gravity, the 235 tractor is stable and comfortable. Equip it with 16 optional attachments and go to work.

- Powerful Hydrostatic Front Wheel Drive
- Easy Foot Controlled Forward and Reverse
- Productive Differential Lock Links Both Drive Wheels for Even Traction
- Maneuverable Rear Wheel Power Steering
- Tight 14-inch Front Wheel Turning Radius
- Steady and Stable Traction-Max™ Weight Transfer System
- Simple Two-Point Quick-Hitch™ Attachment System Requires No Tools
- Handy Auxiliary Hydraulics for Optional Attachments



Slip Scoop



Snow Blower



Tiller

MOW IT ▸ BLOW IT ▸ TRENCH IT ▸ HAUL IT ▸ DRILL IT ▸ TILL IT **DO IT.**

**DO IT.**

## Steiner 235 Tractor Features

<b>Weight Transfer</b>	Trademarked Traction-Max™ Hydraulic Weight Transfer System. Uses the 430 model tractor control valve to charge weight transfer accumulator, with a needle valve added to eliminate pressure leak.
<b>Drive</b>	Robust drive shaft with shock-absorbing element.
<b>Controls</b>	Hi-Low Range selector lever with safety lock on console for easy access.
<b>Power Take-Off</b>	PTO Slider Bracket with round shaft.
<b>Clutch</b>	Large capacity Warner 175 ft lb clutch with large support bearing, with rotation stop.
<b>Tires</b>	6-ply Off-Road 350 Mag front tires.

## Steiner 235 Tractor Specifications

(235D Factory Model number 75-70282; 235G Factory Model number 75-20283)

**Engine:** 235D – Kubota Diesel D1105, 3 Cylinder, 24.8 Gross Horsepower Liquid-cooled, 1123 cc Displacement, 3600 RPM

235G – Briggs and Stratton Vanguard, V-Twin Cylinder, 35 Gross Horsepower Air-cooled, 992 cc Displacement, 3600 RPM

**Charging System:** 40 AMP

**Battery / Ignition:** 235D – 40 AMP Charging System / 12 Volt Battery 620 CCA at zero degrees F / Key Switch Ignition

235G – 50 / 20 AMP Charging System / 12 Volt Battery 525 CCA at zero degrees F / Key Switch Ignition

**Transmission:** Sundstrand Series 15 U-type hydrostatic piston pump motor.

**Transaxle:** 2-speed Peerless 2600 Series with differential lock.

**Traction Boost:** Traction-Max™ adjustable weight transfer with pressure gauge indicator.

**Power Take-Off:** Warner 175 ft lb electric clutch.

**Speeds:**

Forward/Reverse 0-10 MPH (0-16.09 kmh) (high range)  
0-5 MPH (0-8.05 kmh) (low range)

**Steering:** Hydraulic power steering.

**Brakes:** Individual wheel drum turning brakes.

**Lighting:** Dual headlamps. Dual tail lights.

**Seat:** Extra large deluxe contoured seat standard.

**Fuel Tank Capacity:** 6 US gallons.

**Fuel Pump:** Electric

**Tires, Drive:** 24 x 11-2, 350 Mag, 6-ply

**Tires, Rear:** 18 x 8.50-8, Turf Glide ribbed 4-ply

**Attachments:** No tool, Quick-Hitch™ Mounting System.

**Rollover Protective Structure:** Optional

**Warranty:** Two years commercial use. See warranty statement for more details.

**Instrumentation:** Analog: Tachometer and hour meter. Coolant temperature gauge. Fuel gauge. Charging system indicator light.

Indicator Lights: Engine oil pressure. Charging system. Glow plug. PTO.

**Overall Width:** 56 in (147.32 cm)

**Overall Length:** 82 in (208.28 cm)

**Overall Height:** 45 in (114.13 cm)

**Wheelbase:** 50 in (127.0 cm)

**Inside Turning Radius:** 14 in (35.50 cm) (Measured at the front wheel)

**Weight:** 1420 lbs (644.10 kg)

*Specifications, while correct at time of printing, may change without notice.*

## 16 Available Steiner Attachments

**RC646** Rough Cut Mower | **MX460** 60-inch Rotary Mower | **MD472** 72-inch Mower Deck

**MD460** 60-inch Mower Deck | **SB348** Snow Thrower | **MH100** Machinery Hitch

**SS248** 48-inch Slip Scoop | **RS454** Hydro Rotary Sweeper | **BD272** 72-inch Dozer Blade

**BD260** 60-inch Dozer Blade | **TL348** 48-inch Rotary Tiller | **AR240** Core Aerator

**PB200** Turbine Blower | **PB100** Power Blower | **RS350** 54-inch Rotary Sweeper | **BD358** V-Blade



All Steiner products are made with pride in the U.S.A. and are warranted commercially for 2 years. Please see your local dealer for full warranty details also found in the product manual. Your safety is important to us. Before operating any turf maintenance equipment, consult your operator's manual for safe operating and maintenance procedures.

For more information about Steiner products, visit your Steiner dealer today.

For the location of the dealer nearest you, call 1-866-469-1242 or 1-920-699-2000. Visit us on the Web at [www.steinerturf.com](http://www.steinerturf.com).

## 440 TRACTOR SPECIFICATIONS

<b>DIMENSIONS</b>	Overall width: 44.5", 50.5" with 3" wheel extensions, 66.5" with dual wheels   Overall length: 86" with ROPS up Overall height: 73.25" with ROPS up; 50" with ROPS folded   Wheelbase: 43.5"   Minimum ground clearance: 4.75" Frame oscillation: 8"   Turning radius: 44"   Weight: With Kohler® engines: 1489 lb   With Kubota® engines: 1517 lb
<b>ENGINES</b>	440-34KO: Kohler® Command Pro CH904, Air-Cooled, 999 cc 440-40KO: Kohler® Command Pro CH1000, Air-Cooled, 999 cc 440-25KDL: Kubota® D902, Diesel LC, 898 cc 440-32KGL: Kubota® WG972, Gas LC, 962 cc
<b>HYDRAULICS</b>	Pump: Eaton® Series 26   Total capacity (gpm): 6 gpm @ 3600 RPM Lift pressure: 1500 PSI   Hydraulic oil capacity: 5 US Gallons
<b>TRANSMISSION</b>	Drive train: Eaton® Model 70160, Variable displacement piston pump Transaxles: Peerless® 2600 dual range Speeds: 0-10.5 MPH forward, High; 0-5.25 MPH reverse, Low Steering: Hydraulic power steering Brakes: Dual disc and front and rear axles
<b>ATTACHMENT DRIVE</b>	Front PTO clutch: Electric Warner® Mag Stop 225 ft. lb w/ midpole brake Hydraulic outlets: Quick couplers-front
<b>SLOPE RATINGS*</b>	Continuous: 20° Max   Intermittent (10 minutes or less): 30° Max
<b>FUEL SYSTEM</b>	8 US Gallon tank capacity
<b>TIRES</b>	Field Trac 22x12-10   Bar 22x12-10   Turf 22x11-10
<b>HITCH</b>	Front: Steiner Quick-Hitch™ System, with standard front release control or optional release from seated position Back: Standard 2" receiver hitch, with optional category 1 three-point hitch
<b>HIGH-BACK BUCKET SEAT</b>	Armrests: Standard   Suspension: Radial bearing suspension, optional mechanical suspension   Adjustment: 7" fore and aft
<b>ADDITIONAL FEATURES</b>	Lighting: 200 watt halogen quartz headlights (4-50 each), rear marker running lights   Storage Compartment: Standard   Cup holder: Standard PTO tension adjustment: Manual   12 Volt outlet: Optional   Adjustable rear plate positions   Optional hand lever speed control Rollover Protective Structure (ROPS): Standard, folds down



## 235 TRACTOR SPECIFICATIONS

<b>DIMENSIONS</b>	Overall width: 56"   Overall length: 82"   Overall height: 45"   Wheelbase: 50" Inside turning radius: 14" (measured at the front wheel)   Weight: 1420 lb
<b>ENGINE</b>	235D: Kubota® D1105-E3B 3-cylinder, liquid-cooled diesel   68.63" displacement, 3000 RPM, 24.8 gross horsepower
<b>TIRES</b>	Drive: 24x11-2, bar, 6-ply   Rear: 18x8.50-8, turf, 4-ply
<b>DRIVE TRAIN</b>	Transmission: Sauer Danfoss Series 15 U-Type hydrostatic piston pump motor Transaxle: 2-speed Peerless® 2600 Series with differential lock Ground speed: 0-10 MPH forward, High; 0-5 MPH reverse, Low Brakes: Individual wheel drum turning brakes
<b>TRACTION BOOST</b>	Hydraulic Traction-Max™ adjustable weight transfer system with pressure gauge indicator
<b>POWER TAKE-OFF</b>	Warner® 175 ft lb electric clutch
<b>CHARGING SYSTEM</b>	40 AMP battery / Ignition: 12 V   620 CCA
<b>SEAT</b>	Extra-large deluxe contoured seat
<b>LIGHTING</b>	Dual headlights, dual taillights
<b>STEERING</b>	Hydraulic power steering
<b>FUEL SYSTEM</b>	6 US Gallon tank capacity
<b>FUEL PUMP</b>	Electric
<b>ATTACHMENTS</b>	No tools needed, Quick-Hitch™ System
<b>ROLLOVER PROTECTIVE STRUCTURE (ROPS)</b>	Standard



\* Please reference the Product or Owner's Manual for Use Specifications. Slope ratings vary, based on tire and cab configurations.

