

**BEE  
SERIES**

## HOT WATER PRESSURE WASHER

Belt Drive • Electric Powered • Electric Heated

**New Products**



**Same features and  
benefits as current BEE  
series products.**

Model	Coil Material	Motor	KW / AMP	GPM / PSI
H2015BEE3C	Carbon Steel	2 HP / 3PH /460V	36Kv / 48 amp	2.0 gpm 1500 psi
H2015BEE3D	Carbon Steel	2 HP / 3PH /575V	36Kv / 38 amp	2.0 gpm 1500 psi
H3123BEE363C	Carbon Steel	5 HP / 3PH /460V	36Kv / 51 amp	3.1 gpm 2300 psi
H3123BEE363D	Carbon Steel	5 HP / 3PH /575V	36Kv / 41 amp	3.1 gpm 2300 psi
H3123BEE483D	Carbon Steel	5 HP / 3PH /575V	48Kv / 53 amp	3.1 gpm 2300 psi
H3620BEE723C	Carbon Steel	5 HP / 3PH /460V	72Kv / 96 amp	3.6 gpm 2000 psi
H3620BEE723D	Carbon Steel	5 HP / 3PH /575V	72Kv / 77 amp	3.6 gpm 2000 psi
H4030BEE483D	Carbon Steel	7.5 HP / 3PH /575V	48Kv / 56 amp	4.0 gpm 3000 psi
H5030BEE3C	Carbon Steel	10 HP / 3PH /460V	72Kv / 105 amp	5.0 gpm 3000 psi
H5030BEE3D	Carbon Steel	10 HP / 3PH /575V	72Kv / 82 amp	5.0 gpm 3000 psi
H7120BEE3C	Carbon Steel	10 HP / 3PH /460V	72Kv / 105 amp	7.1 gpm 2000 psi
H7120BEE3D	Carbon Steel	10 HP / 3PH /575V	72Kv / 82 amp	7.1 gpm 2000 psi
H3620BEE3CSS	Stainless Steel	5 HP / 3PH /460V	72Kv / 95 amp	3.6 gpm 2000 psi
H3620BEE3DSS	Stainless Steel	5 HP / 3PH /575V	72Kv / 77 amp	3.6 gpm 2000 psi

***Dynablast***<sup>®</sup>

[www.dynablast.ca](http://www.dynablast.ca)



Distributed by:

LPEXPERT 2013 Inc  
1008, rue Marcoux, porte 103  
Granby (QC) J2J 2M8  
[lpexpert@videotron.ca](mailto:lpexpert@videotron.ca) 450 375.3954

# BEE SERIES

## HOT WATER PRESSURE WASHER

Belt Drive • Electric Powered • Electric Heated

- **Downstream Adjustable Chemical Injector:**  
For low pressure soap and chemical injection.
- **Belt Drive Motor and Pump Combination:**  
Maximizes the life of your pump. Protective cover is easily removed for service.
- **Quick Connect Hose Connectors:**  
For easy on/off connections and tangle free hoses.
- **Stainless Steel Hood:**  
Durable rust resistant hood.
- **Large Burner Temperature Dial:**  
Adjust water temperature with ease.
- **Auto Start/Stop:**  
Unit operation controlled with trigger gun.
- **Compact Design:**  
Ideal for storing in tight spaces.

- **All Electric Design Advantages:**  
No re-fueling, no venting, no smoke, no fumes or heat exhaust.



- **Easy Access On/Off Toggle Switch:**  
Includes indicator light.

- **Four Quick Connect Nozzles:**  
Colour coded nozzles included are 0°, 15°, 25°, and soap QC.
- **50' High Pressure Hose:**  
Durable non-marking steel braided hose.
- **Quality Gun and Lance Combination:**  
Easy pull trigger with 48" lance.
- **Hour Meter:**  
Ideal for regular service scheduling maintenance.
- **High Quality Triplex Plunger Pump:**  
All Dynablast pressure washers include GP/Interpump pumps with solid ceramic plungers, thermal pump protector and limited 5 year warranty.
- **Continuous Heat:**  
High efficiency heat exchanger creates constant heat, even after extended use.

### ALL ELECTRIC

SPECIFICATIONS	ASSEMBLED IN CANADA	
MODEL	H4030BEE3C	H4030BEE3D
Operating Pressure (PSI):	3000	3000
Volume (GPM):	4.0	4.0
Engine (HP):	7.5	7.5
Available Voltage (3 Phase):	460	575
Amps:	98	80
KW:	72	72
Pump Speed:	1400	1400
Unit Dimensions (LxWxH):	34"x22"x31"	34"x22"x31"
Unit Weight:	500 lbs	500 lbs

Features and specifications subject to change without prior notice.

#### Other Features:

- **High Pressure Blow Off Valve:**  
For added safety.
- **Baldor Electric ODP Motor**
- **Low Water Shutdown**
- **24 Volt Operating Controls**
- **Solid Steel Casters with Rubber Feet**



[www.dynablast.com](http://www.dynablast.com)

Distributed by:

LPEXPERT 2013 Inc  
1008, rue Marcoux, porte 103  
Granby (QC) J2J 2M8  
[lpexpert@videotron.ca](mailto:lpexpert@videotron.ca) 450 375.3954

# Dynablast®

