440 TRACTOR SPECIFICATIONS

DIMENSIONS **Overall width:** 44.5", 50.5" with 3" wheel extensions, 66.5" with dual wheels | **Overall length:** 86" with ROPS up
Overall height: 73.25" with ROPS up; 50" with ROPS folded | **Wheelbase:** 43.5" | **Minimum ground clearance:** 4.75"
Frame oscillation: 8" | **Turning radius:** 44" | **Weight:** With Kohler® engines: 1489 lb | With Kubota® engines: 1517 lb

ENGINES 440-34KO: Kohler® Command Pro CH904, Air-Cooled, 999 cc
440-40KO: Kohler® Command Pro CH1000, Air-Cooled, 999 cc
440-25KDL: Kubota® D902, Diesel LC, 898 cc
440-32KGL: Kubota® WG972, Gas LC, 962 cc

HYDRAULICS **Pump:** Eaton® Series 26 | **Total capacity (gpm):** 6 gpm @ 3600 RPM
Lift pressure: 1500 PSI | **Hydraulic oil capacity:** 5 US Gallons

TRANSMISSION **Drive train:** Eaton® Model 70160, Variable displacement piston pump
Transaxles: Peerless® 2600 dual range
Speeds: 0-10.5 MPH forward, High; 0-5.25 MPH reverse, Low
Steering: Hydraulic power steering
Brakes: Dual disc and front and rear axles

ATTACHMENT DRIVE **Front PTO clutch:** Electric Warner® Mag Stop 225 ft. lb w/ midpole brake
Hydraulic outlets: Quick couplers-front

SLOPE RATINGS* **Continuous:** 20° Max | **Intermittent (10 minutes or less):** 30° Max

FUEL SYSTEM 8 US Gallon tank capacity

TIRES Field Trac 22x12-10 | Bar 22x12-10 | Turf 22x11-10

HITCH **Front:** Steiner Quick-Hitch™ System, with standard front release control or optional release from seated position
Back: Standard 2" receiver hitch, with optional category 1 three-point hitch



HIGH-BACK BUCKET SEAT **Armrests:** Standard | **Suspension:** Radial bearing suspension, optional mechanical suspension | **Adjustment:** 7" fore and aft

ADDITIONAL FEATURES **Lighting:** 200 watt halogen quartz headlights (4-50 each), rear marker running lights | **Storage Compartment:** Standard | **Cup holder:** Standard
PTO tension adjustment: Manual | **12 Volt outlet:** Optional | Adjustable rear plate positions | Optional hand lever speed control
Rollover Protective Structure (ROPS): Standard, folds down

235 TRACTOR SPECIFICATIONS

DIMENSIONS **Overall width:** 56" | **Overall length:** 82" | **Overall height:** 45" | **Wheelbase:** 50"
Inside turning radius: 14" (measured at the front wheel) | **Weight:** 1420 lb

ENGINE **235D:** Kubota® D1105-E3B 3-cylinder, liquid-cooled diesel | 68.63" displacement, 3000 RPM, 24.8 gross horsepower

TIRES **Drive:** 24x11-2, bar, 6-ply | **Rear:** 18x8.50-8, turf, 4-ply

DRIVE TRAIN **Transmission:** Sauer Danfoss Series 15 U-Type hydrostatic piston pump motor
Transaxle: 2-speed Peerless® 2600 Series with differential lock
Ground speed: 0-10 MPH forward, High; 0-5 MPH reverse, Low
Brakes: Individual wheel drum turning brakes

TRACTION BOOST Hydraulic Traction-Max™ adjustable weight transfer system with pressure gauge indicator

POWER TAKE-OFF Warner® 175 ft lb electric clutch

CHARGING SYSTEM 40 AMP battery / Ignition: 12 V | 620 CCA

SEAT Extra-large deluxe contoured seat

LIGHTING Dual headlights, dual taillights

STEERING Hydraulic power steering

FUEL SYSTEM 6 US Gallon tank capacity

FUEL PUMP Electric

ATTACHMENTS No tools needed, Quick-Hitch™ System

ROLLOVER PROTECTIVE STRUCTURE (ROPS) Standard



** Please reference the Product or Owner's Manual for Use Specifications. Slope ratings vary, based on tire and cab configurations.*

440 TRACTOR SPECIFICATIONS

MODELS 440-32KO, 440-37KO, 440-25KDL, 440-32KGL



Dimensions:

Overall Width: 44.5", 66.5" with dual wheels
Overall Length: 80.5" with ROPS up
Overall Height: 73.25" with ROPS up
50" with ROPS folded
Wheelbase: 43.5"
Minimum Ground Clearance: 4.75"
Frame Oscillation: 8"
Frame Articulation: 36 degrees, 44" turning radius

Hydraulics:

Pump: Eaton® Series 26
Total Capacity (gpm): 6 gpm @ 3600 RPM
Lift Pressure: 1500 PSI
Hydraulic Oil Capacity: 5 US Gallons

Transmission:

Drive Train: Eaton® model 70160, Radial Axle Piston Pump
Transaxles: Peerless® 2600 Dual Range
Speeds: 0-10.5 MPH, High; 0-5.25 MPH, Low
Steering: Hydraulic Power Steering
Brakes: Dual Disc and front and rear axles

Attachment Drive:

Front PTO Clutch: Electric Warner® Mag Stop 225 Ft. Lb w/ Midpole Brake
Hydraulic Outlets: Quick Couplers-Front

Fuel System:

8 US Gallon Tank Capacity

Wheels:

38 Special (Fieldtrax) 22x12-10
Mag Off Road (Bar) 22x12-10
GrassMaster (Turf) 22x11-10

Hitch:

Front: Steiner Quick-Hitch, with standard front release control or optional release from seated position
Back: Standard 2" receiver hitch, with optional category 1 compatible three-point hitch

High-Back Bucket Seat:

Armrests: standard
Suspension: Radial Bearing Suspension, optional Mechanical Suspension
Adjustment: 7" Fore and Aft

Additional Features:

Lighting: 200 watt halogen quartz headlights (4-50 each), rear marker running lights
Storage Compartment: Standard
Cup Holder: Standard
PTO Tension Adjustment: Manual
12 Volt Outlet: Optional

MODEL SPECIFICATIONS

Models	440-32KO	440-37KO	440-25KDL	440-32KGL
Weight:	1489	1489	1517	1517
Engine:	Kohler® Command Pro CH940, Air-Cooled	Kohler® Command Pro CH1000, Air-Cooled	Kubota® D902, Diesel LC	Kubota® WG972, Gas LC
HP @ RPM*:	32.5 HP gross @ 3600 RPM	37 HP gross @ 3600 RPM	24.8 (gross intermittent) @ 3600 RPM	32.4 (gross intermittent) @ 3600 RPM
Engine Cyls & Displacement:	2 cyl, 999cc (61 cu. in.)	2 cyl, 999cc (61 cu. in.)	3 cyl, 898cc (54.8 cu. in.)	3 cyl, 962cc (58.7 cu. in.)
Alternator/Amps:	40 Amp	40 Amp	40 Amp	40 Amp
Battery/Cold Cranking Amps:	12V - 525 Cold Cranking Amps	12V - 525 Cold Cranking Amps	12V - 630 Cold Cranking Amps	12V - 525 Cold Cranking Amps
Standard Instrumentation:	Tachometer Hour Meter Low Oil Pressure Indicator Voltmeter Parking Brake PTO Switch Driving Lights Switch	Tachometer Hour Meter Low Oil Pressure Indicator Voltmeter Parking Brake PTO Switch Driving Lights Switch	Tachometer Hour Meter Engine Coolant Temp Low Oil Pressure Indicator Voltmeter Glow Plug Light Parking Brake PTO Switch Driving Lights Switch	Tachometer Hour Meter Engine Coolant Temp Low Oil Pressure Indicator Voltmeter Parking Brake PTO Switch Driving Lights Switch

* Engine HP is per SAE ratings for Kubota® Per SAE-1939. Kohler® Per SAE-1940.

Steiner® uses commericial-strength engine options for longevity and ease of service. All engines are warranted by their respective manufacturer and your local dealer.
The power engine ratings are provided by the engine manufactuer. Actual power output is dependent on many factors including engine rpm, air density and engine condition.

All Steiner® products are made with pride in the U.S.A. and are warranted commercially for 2 years. Please see your local dealer for full warranty details also found in the product manual. Your safety is important to us. Before operating any turf maintenance equipment, consult your operator's manual for safe operating and maintenance procedures.

For more information about Steiner® products, visit your Steiner® dealer today.
For the location of the dealer nearest you, call 1-866-469-1242 or 1-920-699-2000.
Visit us on the Web at www.steinerturf.com and visit YouTube to see the Steiner 440.



- **The 440 4-wheel Drive Tractor is tough and powerful... and yet it retains the compact, highly maneuverable and easily versatile attributes of its predecessor, the 430. Most attachments for Steiner® 430 and 235 Front Wheel Drive tractors are interchangeable with the 440.**
- **The 440 has impressive engine horsepower, and hydraulic power available for work, with extensive front attachments and an optimal rear category I compatible 3-point hitch, and yet is comfortable with controls that are more accessible and easier to use.**
- **The 440 has a higher power to weight ratio than its nearest competitor and offers more "Get it Done" Power in a smaller, more versatile machine.**
- **The 440 is balanced, so less weight is needed to counter balance front attachments, resulting in well distributed weight on the ground and less compaction.**

Steiner® is a registered trademark of Schiller Grounds Care, Inc.
©2018 Schiller Grounds Care, Inc. Company. All rights reserved. Steiner I One BOB-CAT Lane I Johnson Creek, WI 53038

440 4-WHEEL DRIVE TRACTOR

WITH ARTICULATING POWER STEERING & OSCILLATING FRAME

POWERFUL ENGINE CHOICES

Kohler: 32.5 or 37 HP Air-Cooled
Kubota: 25 HP Diesel or 32 HP Gas Liquid-Cooled
40 AMP Alternator / 525 CCA Battery (630 Dsl)

STRONG HYDRAULIC POWER

Dual pumps deliver power and efficient cooling. An immpressive 5 gpm/1500 psi auxiliary circuit provide strong lift capacity and accessory power.
More available hydraulic power for steering and work

STRONGER FRONT AND REAR TRANSAXLES

Twice as strong as the 430
Dual Range 10 MPH Forward / 5.25 Reverse

EASIER OPERATION

Foot Control Forward and Reverse
200 Watt Headlights
8.0 Gallon Fuel Capacity — EPA Compliant

COMFORTABLE

Larger Operator Platform adjusts vertically
Standard Radial Seat Springs, Optional Suspension Kit
Arm Rests Standard

MORE STANDARD FEATURES

Folding Rollover Protective Structure
Integral Frame Weight Bar
Dual Range Transaxles for Torque and Speed

EASILY AND COMPLETELY VERSATILE

Simple Front Two-Point Quick-Hitch — No Tools!
New Traction-Assist Adjusts from the seat

OPTIONAL ACCESSORIES

Category 1 compatible 3 Pt. Hitch
Dual Wheel Sets — Turf, Bar Tread, All Terrain
Deluxe Cab Enclosure
Wheel Extensions




TOUGH. POWERFUL.









STEINER